

Revision Number: 002.1

Issue date: 07/21/2009

IDH number:702133Item number:83094_AA0615Region:United StatesContact information:			
Telephone: 860.571.5100 Emergency telephone: 860.571.5100 Internet: www.henkelna.com			
. HAZARDS IDENTIFICATION			
EMERGENCY OVERVIEW HMIS: HEALTH: *2 FLAMMABILITY: 1 PHYSICAL HAZARD: 0 Personal Protection: See MSDS Section 8 USE ALLERGIC SKIN REACTION. USE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.			
Relevant routes of exposure: Skin, Inhalation, Eyes Potential Health Effects Mild respiratory tract irritation. May cause irritation to nose and throat. Coughing.			
ic skin reaction. Moderate skin irritation. Itching. Redness. Swelling. cause irritation. If left untreated, corneal damage can occur and injury is slow to heal. xpected under normal conditions of use. skin and respiratory disorders. Skin allergies. material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR			

See Section 11 for additional toxicological information.

3. (3. COMPOSITION / INFORMATION ON INGREDIENTS			
ponents	C	CAS NUMBER	%	

Hazardous components	CAS NUMBER	%
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	30 - 60
Quartz (SiO2)	14808-60-7	10 - 30
Talc	14807-96-6	5 - 10
Dibutyl phthalate	84-74-2	1 - 5
Treated fumed silica	67762-90-7	1 - 5

4. FIRST AID MEASURES

Inhalation:

Skin contact:

Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Gemedical attention.		
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Keep individual calm. If symptoms develop and persist, get medical attention.	
5. F	IRE FIGHTING MEASURES	
Flash point:	248.9 °C (480.02 °F) Pensky Martens closed cup	
Autoignition temperature:	Not available	
Flammable/Explosive limits - lower:	Not available	
Flammable/Explosive limits - upper:	Not available	
Extinguishing media:	Foam, dry chemical or carbon dioxide.	
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.	
Unusual fire or explosion hazards:	In case of fire, keep containers cool with water spray. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.	
Hazardous combustion products:	Oxides of carbon. Irritating organic fragments.	
6. ACCIDENTAL RELEASE MEASURES		

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.	
Clean-up methods:	Remove all sources of ignition. Immediately contact emergency personnel. Scrape up as much material as possible. Clean residue with soap and water. Store in a partly filled, closed container until disposal.	
7. HANDLING AND STORAGE		

Handling:	Keep away from heat, spark and flame. Do not breathe gas/fumes/vapor/spray. Keep container closed. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.
Storage:	Store in original container until ready to use. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None
Talc	2 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	50 ppm
Dibutyl phthalate	5 mg/m3 TWA	5 mg/m3 TWA	None	None
Treated fumed silica	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.				
Respiratory protection:	Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.			
Eye/face protection:	Safety goggles or safety glasses with side shields.			
Skin protection:	Chemical resistant, impermeable gloves.			
9. PHYSICAL AND CHEMICAL PROPERTIES				

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Paste Blue None Not available Not applicable Not available > 260 °C (> 500°F) Not available 1.17 Not available 248.9 °C (480.02 °F) Pensky Martens closed cup Not available Not available Not available Not available Not miscible or difficult to mix Not available < 0.1 % (value for resin and hardener together) (estimated)

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	None
Incompatible materials:	Strong acids. Strong bases. Strong oxidizing agents. Amines. Water.
Conditions to avoid:	Avoid temperatures above 38°C (100°F). Excessive heat. Store away from incompatible materials. Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately. Failure to observe these precautions may result in excessive heat build-up causing an exotherm.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Quartz (SiO2)	Known carcinogen.	Group 1	No
Talc	No	No	No
Dibutyl phthalate	No	No	No
Treated fumed silica	No	No	No

Hazardous components	Health Effects/Target Organs
Epichlorohydrin-4,4'-isopropylidene diphenol resin	Allergen, Irritant
Quartz (SiO2)	Immune system, Lung, Some evidence of carcinogenicity
Talc	Irritant, Lung, Some evidence of carcinogenicity
Dibutyl phthalate	Central nervous system, Developmental, Irritant, Reproductive
Treated fumed silica	Irritant

12. ECOLOGICAL INFORMATION

Ecological information:

Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:

Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR) Proper shipping name: Not reg

Not regulated
None
None
None

International Air Transportation (ICAO/IATA)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group:	Not regulated None None None	
	15. REGULATORY INFORMATION	
	15. REGULATORT INFORMATION	
United States Regulatory Information		
TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.	
TSCA 12(b) Export Notification:	None above reporting de minimus	
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None above reporting de minimus Immediate Health, Delayed Health This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Dibutyl phthalate (CAS# 84-74-2).	
CERCLA Reportable quantity:	Dibutyl phthalate (CAS# 84-74-2) 10 lbs. (4.54 kg)	
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
Canada Regulatory Information		
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.	
WHMIS hazard class:	D.2.A, D.2.B	
16. OTHER INFORMATION		

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Gary Pierson, Sr. Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.